

3566 SERIES ALKYD ZONE MARKING PAINT

1. PRODUCT NAME

3566 SERIES ALKYD ZONE MARKING PAINT

2. MANUFACTURER

SIERRA LLC

11400 West 47th Street

Minnetonka, MN 55343

952-938-7223

952-938-8084 (FAX)

Website: <http://www.sierrapaint.com>

3. PRODUCT DESCRIPTION

3566 ALKYD ZONE MARKING PAINT is a solvent base, alkyd zone marking paint for use on asphalt and concrete. Its fast drying formula allows for quick reopening of high traffic areas while being durable enough to resist tire pick-up and scuffing due to high traffic. Its vibrant, high gloss finish is available in a variety of long-lasting colors including; White, Yellow, Black and "Handicap Blue".

When tested against competing zone marking products, 3566 ALKYD ZONE MARKING PAINT has been shown to provide superior performance by lasting longer and staying cleaner.

4. TECHNICAL DATA

Composition and Materials:

Alkyd zone marking paint.

Color:	White, Yellow, Black, "Handicap Blue"
Packaging:	5-gallon metal pail 55-gallon lined drum
Solvent Type:	Alkyd
Gloss at 60°:	25 - 40
% Solids:	52 - 56%
Viscosity at 77°F:	59 - 60 KU
Dry Time	
Tack Free:	30 minutes
Recoat:	2 hours
Full Cure:	8 hours
Flash Point:	-15°F
VOC Content:	< 450 g/l (3.76 lb/gallon)

5. APPLICATION PROCEDURES AND INSTRUCTIONS

Preparation:

Surface should be in sound condition, clean and dry and at a temperature between 32°F-90°F. Any repairs should be made before coating.

Mixing:

Products is supplied ready to use but should be stirred prior to use to eliminate any phase separation or settling which may occur upon shipping and storage.

Application:

Because of its fast drying properties, the product is best applied by airless spray but may also be applied by conventional air spray, brush or roller.

Coverage:

350 - 400 ft²/gallon.

Cleanup:

Clean tools and spills with xylene before the material dries.

Precautions:

This product contains organic solvents which have associated health and fire hazards. Minimize exposure by always wearing appropriate personal protection equipment. Keep away from sparks, open flame or any source of ignition. Keep out of reach of children. Dispose of empty containers in accordance with all applicable regulations.

Before using any product, always read the product's Safety Data Sheet (SDS).

CONDITIONS OF SALE/ LIMITED WARRANTY5 YEAR MATERIAL WARRANTY UPON REQUEST

SIERRA LLC, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of Sierra' product by others and other factors affecting product performance are beyond Sierra's control, Sierra does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY SIERRA PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, SIERRA WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF SIERRA PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. Sierra does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by Sierra in writing.

SIERRA LLC



11400 West 47th Street Minnetonka, MN 55343

800-441-2129 toll free | 952-938-8084 fax | www.sierrapaint.com