

FEBRUARY 1, 2010

## **TK-5765 SILOXANE DYE**

### ***Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation***

TK-5765 SILOXANE DYE is a waterborne spray applied flexible air/vapor barrier membrane for all types of cavity wall construction. It meets or exceeds ASTM E-2178 for air leakage and ASTM E-96 for water vapor permeability.

**TK Products certifies the following information for TK-5765 SILOXANE DYE:**

#### **Manufacturing Location**

TK-5765 SILOXANE DYE is manufactured in Minnetonka, MN.

#### **Regional Materials**

25% by weight of TK-5765 SILOXANE DYE was produced with regionally extracted and processed materials.

#### **Recycled Content**

TK-5765 SILOXANE DYE is manufactured with 6% combined recycled content.

#### **VOC Content**

TK Products certifies that the VOC (volatile organic content) of TK-5765 SILOXANE DYE is 774g/l.

***Based upon the above information, TK Products certifies that TK-5765 SILOXANE DYE may contribute to the following LEED NC v2.2 Credits:***

- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured

Respectfully,



LEED Administrator  
TK Products  
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council