

FEBRUARY 1, 2010

## **TK-1900 WB URETHANE**

### ***Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation***

TK-1900 WB URETHANE is a water-borne, non-yellowing, 100% aliphatic urethane for sealing concrete. Because it has superior chemical, abrasion, and water blush resistance it is recommended for areas requiring special resistance properties.

**TK Products certifies the following information for TK-1900 WB URETHANE:**

#### **Manufacturing Location**

TK-1900 WB URETHANE is manufactured in Minnetonka, MN.

#### **Regional Materials**

25% by weight of TK-1900 WB URETHANE was produced with regionally extracted and processed materials.

#### **Recycled Content**

TK-1900 WB URETHANE is manufactured with 6% combined recycled content.

#### **VOC Content**

TK Products certifies that the VOC (volatile organic content) of TK-1900 WB URETHANE is 385g/l.

***Based upon the above information, TK Products certifies that TK-1900 WB URETHANE may contribute to the following LEED NC v2.2 Credits:***

- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured

Respectfully,



LEED Administrator  
TK Products  
Tel: 800-441-2129

*LEED is a trade mark of the US Green Building Council*