

APRIL 24, 2009

TK-5329 FLOOR HARDENER AND DENSIFIER

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

TK-5329 FLOOR HARDENER & DENSIFIER is a high solids sodium silicate, hardening and densifying, and sealing agent for concrete. On existing concrete, the inner chemical reaction forms a hardened, dustproof surface.

TK Products certifies the following information for TK-5329 FLOOR HARDENER & DENSIFIER:

Manufacturing Location

TK-5329 FLOOR HARDENER & DENSIFIER is manufactured in Minnetonka, MN.

Recycled Content

TK-5329 FLOOR HARDENER & DENSIFIER is manufactured with 6% of pre-consumer material recycled content from the normal recovery of raw material in manufacturing process.

VOC Content

TK Products certifies that the VOC (volatile organic content) of TK-5329 FLOOR HARDENER & DENSIFIER is 0g/l.

Based upon the above information, TK Products certifies that TK-5329 FLOOR HARDENER & DENSIFIER may contribute to the following LEED NC v2.2 Credits:

- MR Credits 1.1 & 1.2: Building Reuse: Maintain 75% & 95% of Existing Walls, Floors, & Roof
- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council