



TK-TRI-GRIP

Non-Slip Synthetic Aggregate

Item No. TK-TRI GRIP

PRODUCT DESCRIPTION

TK-TRI-GRIP is a synthetic aggregate made up of clear polypropylene spheres that creates a subtly textured, slip resistant surface on new or existing concrete and masonry surfaces.

Features:

- Creates a textured surface without sharp edges, lumps or bumps.
- Increases safety and peace of mind in areas prone to becoming slippery.
- Lightweight polypropylene spheres stay easily suspended in curing and sealing compounds, stains, epoxies and urethanes.
- Clear particles are unnoticeable on the floor.

USES:

Suitable for interior or exterior use on new and existing commercial, industrial or residential concrete flooring. It is ideal near entrance doors and walkways, garage floors, driveways, patios, steps, or any concrete surface that may become slippery.

APPLICATION PROCEDURES:

PREPARATION:

Clean the concrete floor of any dirt, oil, or other contaminants. Use TK-CHEMICAL CLEANER 101* or other suitable cleaner to remove grease or oil stains. Rinse well, and let the concrete floor dry completely.

MIXING:

TK-TRI-GRIP comes pre-packaged in a 1-pound container. Shake or stir the container before application to bring the aggregate back up in suspension. Shake or stir during use to keep the aggregate in suspension. TK-TRI-GRIP may be added to TK's coating compounds up to 12 hours prior to application. Add one container of TK-TRI-GRIP to 5-gallons of any TK Products cure, seal, colored stain, epoxy or urethane for standard texture result.

More or less textured results may be achieved by the following:

- For more texture, double the amount of TK-TRI-GRIP to two 1-pound containers.
- For less texture, reduce the amount of TRI-GRIP to half of a 1-pound container.

APPLICATION:

Once mixed with a coating compound, TK-TRI-GRIP may be brushed, rolled or sprayed on concrete surfaces (if spraying, use a large tip size, as used for white pigmented sealers). TK-TRI-GRIP produces a light texture and may be applied in more than one coat - if applying a second coat, do not apply a TK coating without TK-TRI-GRIP added as it will inhibit a textured finish from being achieved.

TECHNICAL DATA

Composition and Materials:	Polypropylene in small sphere shaped particles.
A.I.M. Category:	This product is not currently regulated by 1999 Federal EPA VOC regulations

COVERAGE:

Typical coverage rate is 200-400 square feet per gallon. Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

MAINTENANCE:

TK-TRI-GRIP is a synthetic resin and is subject to wear. Areas of the concrete floor that show signs of wear may be recoated to rejuvenate the texture.

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

AVAILABILITY:

TK-TRI-GRIP is available through TK Distributors. Contact TK Products for the nearest distributor.

Packaged in one pound containers - enough for mixing with 5-gallons of aTK Products coating compound.

FOR PROFESSIONAL USE ONLY

03/15 Last Rev. 09/14

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. **SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED.** TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.

TK Products Construction Coatings

11400 West 47th Street Minnetonka, MN 55343
800-441-2129 toll free | 952-938-8084 fax | www.tkproducts.com

