



VOC Regulatory Compliance:



ISO 9001 CERTIFIED

### PRODUCT DESCRIPTION

TK-BRIGHT SEAL WB is an acrylic, waterborne, high solids sealer for new or existing decorative concrete. TK-BRIGHT SEAL WB brings out the "wet look" and highlights the natural pigments in the surface, all while protecting it against abrasion and damage.

#### Features:

- Dries clear with the glossy "wet look" finish sought after for decorative concrete surfaces.
- Highlights colored and decorative surfaces.
- UV stable
- Ideal for use on interior surfaces where harsh solvent based systems cannot be tolerated.
- Seals, protects and dustproofs.
- Compatible with most tile and carpet adhesives and can be used to seal many types of porous tile and resilient floors.

#### USES:

Suitable for interior or exterior use on new or existing concrete floors, walls, columns, pavers, burnished block or exposed aggregate. Ideal for use in industrial, commercial, residential or institutional environments.

### APPLICATION PROCEDURES

#### PREPARATION:

TK-BRIGHT SEAL WB is ready for use. Do not dilute. Surfaces must be clean, dry and free of foreign contaminants. Sweep or vacuum to remove dirt or dust, or use TK-CHEMICAL CLEANER 101\* to clean the surface of oils, grease, stains, wax or polish. Curing compounds and sealers should be removed with a solvent as they could inhibit the development of the "wet look" when applying TK-BRIGHT SEAL WB. Rinse thoroughly and allow surface to fully dry.

A test panel mock-up should be performed prior to project start up to determine coverage rates, proper appearance and results. Apply enough TK-BRIGHT SEAL WB to satisfy the porosity of the substrate while leaving a thin film on the surface.

Steel Troweled Surface Preparation - Surface should be acid etched or shot blasted to promote better adhesion.

#### APPLICATION PROCEDURE:

For Horizontal Surfaces: May be applied by low pressure sprayer and back rolled. It may also be applied with a roller or brush in small areas. Apply in a uniform manner and at the specified application rate, taking care to avoid lap marks. Use natural break points, such as cuts and joints as stopping points whenever possible. DO NOT OVER APPLY.

For Vertical Surfaces: For best results, apply with an airless sprayer and back roll. Apply in a uniform manner at the

## TK-BRIGHT SEAL WB

### Waterborne Decorative Concrete Sealer

Item No. TK-BRSEAL WB

#### TECHNICAL DATA

Composition and Materials:	Fine quality, pliable acrylic polymers in an aqueous system. Carefully blended and quality controlled, it contains no oils, saponifiable resins or waxes.
Color:	Clear
Drying Time* (70°F & 50% RH): Tack Free: Open to Traffic:	1-2 hours 4-12 hours
V.O.C. Content:	< 400 g/L
A.I.M. Category:	Sealers Maximum VOC 400 g/l
Applicable Standards:	-ASTM C-309, Type 1, Class A & B and Type 1D with a red dye added -AASHTO Des. M-148, Type 1, Clear -ACI Standard 302-77 for use on Class 1, 2, 3 and 4 concrete floors. - USDA Authorization for use in meat, poultry, and food processing plants

\* Cooler temperatures and high humidity rates will extend drying time

specified application rate, taking care to avoid lap marks. Use natural break points, such as cuts and joints as stopping points whenever possible. DO NOT OVER APPLY.

#### CLEAN UP:

Use soap and water before the material has dried. If the material is already dry, use MEK or Xylene (methyl ethyl ketone) to remove.

#### COVERAGE:

Surface	Coverage
Exposed Aggregate:	300 - 500 sq.ft./gal
Broomed Finish:	300 - 500 sq.ft./gal
Troweled Finish:	300 - 500 sq.ft./gal
Second Coat (if necessary):	300 - 500 sq.ft./gal

Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

#### MAINTENANCE:

Any stains or spills should be removed as soon as possible. TK-BRIGHT SEAL WB may be reapplied to areas that are worn or where spills have removed the sealer.

**LIMITATIONS:**

- Apply in temperatures above 50°F.
- Protect from freezing.
- Do not apply to exterior horizontal surfaces that pond water as this may cause a blushing to occur.
- Not for use on asphalt or surfaces where spillage of solvents, fuels, brake or transmission fluids are expected.
- Avoid heavy accumulations as this can cause slippery conditions or a lifting action between coats.

**FIRST AID:**

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

**AVAILABILITY:**

TK-BRIGHT SEAL WB is available through TK Distributors. Contact TK Products for the nearest distributor.

Packaged in 55-gallon drums, 5-gallon pails and 1-gallon cans.

FOR PROFESSIONAL USE ONLY

**NOTES:**

\*TK-CHEMICAL CLEANER 101 must be purchased separately

**CONDITIONS OF SALE/ LIMITED WARRANTY**

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. **SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED.** TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

**TK DISCLAIMER:**

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also **CONDITIONS OF SALE/ LIMITED WARRANTY** (Section 7) above.

11/16 Last Rev. 03/01